$CS-Q^{\scriptscriptstyle\mathsf{TM}}$

wallspeaker

In classrooms where recessed ceiling speakers are not practical, the CS-Q™ wall speaker is an excellent alternative. Lightweight, sturdy and easy to install, these speakers deliver superb full-range sound with optimum clarity.


Two CS-Q[™] wall speakers and a LightSPEED Classroom Amplification System are all that is needed to guarantee that everyone hears the same great audio quality throughout the classroom.




■ overview
■ room coverage
■ profile

Two CS-Q[™] wall speakers are ideal for classrooms of up to 1200 square feet with 8 to 12 foot ceilings.

- New Curved Design
- Two Speakers Fill Entire Room
- Elegant Cabinet Styling
 Protected by Steel Mesh
- Delivers a rich, full sound



Top View of Room Covers up to 1200 sq. ft. (Example: 30 ft. x 40 ft.)



CS-Q"	wall speaker specifications	
Speaker Type		
Frequency Response	110 Hz −20 kHz ±6 d	lΒ
Impedance		
Power Handling	10 W	
SPL @ 1w/1m	94 dB	
Dimensions (L x H x D inc	ches) 13 x 9.45 x 3.54	
Weight	1.56 lbs.	



www.lightspeed-tek.com

imagine...